

VOLUME 4: APPENDIX V1-3.1: INDICATIVE TOWER SCHEDULE – PROPOSED ALIGNMENT

SSE DRAWING NUMBER :										TOWER SCHEDULE										LSTC DOC REF : 02_230796_12 RevG																																																																																																																																																															
Scottish & Southern Electricity Networks TRANSMISSION										<table><tr><td>LINE</td><td colspan="9">Strathy Wood - Connagill (Towers 19 to 64)</td></tr><tr><td>VOLTAGE</td><td colspan="9">132kV / 275kV</td></tr><tr><td>No 1 CIRCUIT ID</td><td colspan="9">Strathy Wood</td></tr><tr><td>No 1 CIRCUIT COLOUR CODE</td><td>T.B.C</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>No 2 CIRCUIT ID</td><td colspan="9">Strathy South</td></tr><tr><td>No 2 CIRCUIT COLOUR CODE</td><td>T.B.C.</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>										LINE	Strathy Wood - Connagill (Towers 19 to 64)									VOLTAGE	132kV / 275kV									No 1 CIRCUIT ID	Strathy Wood									No 1 CIRCUIT COLOUR CODE	T.B.C									No 2 CIRCUIT ID	Strathy South									No 2 CIRCUIT COLOUR CODE	T.B.C.									<table><tr><td>PHASE CONDUCTOR SIZE</td><td colspan="9">500mm² AAAC RUBUS</td></tr><tr><td>EARTHWIRE CONDUCTOR SIZE / OPGW</td><td colspan="9">48f OPGW KEZIAH EQ.</td></tr><tr><td>MINIMUM GROUND CLEARANCE</td><td colspan="9">6.7m / 7.0m</td></tr><tr><td>DESIGN TEMPERATURE</td><td colspan="9">90°C</td></tr><tr><td>CONTRACTOR</td><td colspan="9">T.B.C.</td></tr><tr><td>CONSTRUCTION DATE</td><td colspan="9">T.B.C.</td></tr></table>										PHASE CONDUCTOR SIZE	500mm² AAAC RUBUS									EARTHWIRE CONDUCTOR SIZE / OPGW	48f OPGW KEZIAH EQ.									MINIMUM GROUND CLEARANCE	6.7m / 7.0m									DESIGN TEMPERATURE	90°C									CONTRACTOR	T.B.C.									CONSTRUCTION DATE	T.B.C.									<table><tr><td rowspan="3">STRATHY WOOD PHASE COLOURING:</td><td>TOP:</td><td rowspan="3">T.B.C.</td></tr><tr><td>MIDDLE:</td></tr><tr><td>BOTTOM:</td></tr><tr><td rowspan="3">STRATHY SOUTH PHASE COLOURING:</td><td>TOP:</td><td rowspan="3">T.B.C.</td></tr><tr><td>MIDDLE:</td></tr><tr><td>BOTTOM:</td></tr></table>										STRATHY WOOD PHASE COLOURING:	TOP:	T.B.C.	MIDDLE:	BOTTOM:	STRATHY SOUTH PHASE COLOURING:	TOP:	T.B.C.	MIDDLE:	BOTTOM:	LSTC GROUP Scottish & Southern Electricity Networks TRANSMISSION									
LINE	Strathy Wood - Connagill (Towers 19 to 64)																																																																																																																																																																																		
VOLTAGE	132kV / 275kV																																																																																																																																																																																		
No 1 CIRCUIT ID	Strathy Wood																																																																																																																																																																																		
No 1 CIRCUIT COLOUR CODE	T.B.C																																																																																																																																																																																		
No 2 CIRCUIT ID	Strathy South																																																																																																																																																																																		
No 2 CIRCUIT COLOUR CODE	T.B.C.																																																																																																																																																																																		
PHASE CONDUCTOR SIZE	500mm² AAAC RUBUS																																																																																																																																																																																		
EARTHWIRE CONDUCTOR SIZE / OPGW	48f OPGW KEZIAH EQ.																																																																																																																																																																																		
MINIMUM GROUND CLEARANCE	6.7m / 7.0m																																																																																																																																																																																		
DESIGN TEMPERATURE	90°C																																																																																																																																																																																		
CONTRACTOR	T.B.C.																																																																																																																																																																																		
CONSTRUCTION DATE	T.B.C.																																																																																																																																																																																		
STRATHY WOOD PHASE COLOURING:	TOP:	T.B.C.																																																																																																																																																																																	
	MIDDLE:																																																																																																																																																																																		
	BOTTOM:																																																																																																																																																																																		
STRATHY SOUTH PHASE COLOURING:	TOP:	T.B.C.																																																																																																																																																																																	
	MIDDLE:																																																																																																																																																																																		
	BOTTOM:																																																																																																																																																																																		
TOWER				SPAN LENGTH (m)	WIND SPAN	SECTION LENGTH (m)	ANGLE OF DEVIATION (+ve RIGHT -ve LEFT)	CHAINAGE	GROUND LEVEL	STRUCTURE HEIGHT (G.L. TO PEAK)	ATT.PT (BASED ON TYPICAL SUSP'N INSULATOR)	PHASE INSULATORS					OPGW INSULATORS				PROFILE DRAWING REF.	ROUTE CENTRELINE COORDINATES		JUMPER WEIGHTS - CCT1	JUMPER WEIGHTS - CCT2	VIBRATION DAMPERS - PHASES	VIBRATION DAMPERS - OPGW	CROSSINGS / INFRINGEMENTS IN SPAN	REMARKS	TOWER NO																																																																																																																																																					
NO	SPEC	TYPE	BODY EXT									NO OF STRINGS	UNIT RATING	UNITS PER STRING	ARC GAP	DRAWING REF.	CONDUCTOR TERMINATION	ADDITIONAL INSULATOR WEIGHT (IF REQ)	UNIT RATING	DRAWING REF.	CONDUCTOR TERMINATION		EASTING	NORTHING																																																																																																																																																											
19	L7C	DJT	STD		278.55	517.42	50.10	4478.09	45.13	28.12												282837.20	960415.83							WORKING AREA: 70m x 70m & PROPOSED CONDUCTOR PULLING POSITION	19																																																																																																																																																				
20	L7C	D	E3	261.63	258.71			4739.72	47.79	29.95													282975.73	960637.78							WORKING AREA: 50m x 50m	20																																																																																																																																																			
21	L7C	D30	E3	255.79	254.20		-22.12	4995.51	61.94	29.21													283111.16	960854.77					ACCESS TRACK	WORKING AREA: 70m x 70m	21																																																																																																																																																				
22	L7C	D	E3	252.61	250.85	1238.16		5248.12	66.10	29.95												283154.37	961103.66							WORKING AREA: 50m x 50m	22																																																																																																																																																				
23	L7C	D	E3	249.09	249.00			5497.21	70.66	29.95													283196.97	961349.07							WORKING AREA: 50m x 50m	23																																																																																																																																																			
24	L7C	D	E3	248.92	246.17			5746.13	84.99	29.95													283239.54	961594.32							WORKING AREA: 50m x 50m	24																																																																																																																																																			
25	L7C	D	E3	243.41	243.77	457.51		5989.54	81.25	29.95												283281.18	961834.15							WORKING AREA: 50m x 50m	25																																																																																																																																																				
26	L7C	D60	E9	244.13	237.83		59.74	6233.67	58.24	35.15													283322.93	962074.68					BURN	WORKING AREA: 70m x 70m & PROPOSED CONDUCTOR PULLING POSITION	26																																																																																																																																																				
27	L7C	D	E15	231.52	228.76			6465.19	60.57	42.14													283539.92	962155.43							WORKING AREA: 50m x 50m	27																																																																																																																																																			
28	L7C	D30	E3	225.99	234.77	243.55	1.02	6691.18	97.42	29.21												283751.72	962234.24							WORKING AREA: 70m x 70m	28																																																																																																																																																				
29	L8C	DJT	STD	243.55	243.37			6934.73	101.91	48.24													283981.44	962315.12							WORKING AREA: 80m x 80m	29																																																																																																																																																			
30	L8C	D	E7.3	243.19	241.46			7177.92	96.21	53.75													284210.83	962395.88							WORKING AREA: 50m x 50m	30																																																																																																																																																			
31	L8C	D10	E3.7	239.73	247.38	2036.62	1.23	7417.65	118.94	47.47												284436.96	962475.49							WORKING AREA: 80m x 80m	31																																																																																																																																																				
32	L8C	D	M2.4	255.03	263.77			7672.68	132.81	43.99													284679.29	962554.98							WORKING AREA: 50m x 50m	32																																																																																																																																																			
33	L8C	D	E4.9	272.52	249.47			7945.20	131.72	51.31													284938.23	962639.93							WORKING AREA: 50m x 50m	33																																																																																																																																																			
34	L8C	D	M4.9	226.42	253.43	275.47		8171.61	146.97	41.55												285153.36	962710.50							WORKING AREA: 50m x 50m	34																																																																																																																																																				
35	L8C	D	E6.1	280.44	259.37			8452.05	129.08	52.53													285419.83	962797.92							WORKING AREA: 50m x 50m	35																																																																																																																																																			
36	L8C	D	STD	238.30	267.51			8690.35	125.89	46.43													285646.25	962872.20							WORKING AREA: 50m x 50m	36																																																																																																																																																			
37	L8C	D	E3.7	296.73	260.97	254.65		8987.08	129.36	50.09												285928.20	962964.69					ACCESS TRACK	WORKING AREA: 50m x 50m	37																																																																																																																																																					
38	L8C	D	M4.9	225.22	233.60			9212.30	143.18	41.55													286142.20	963034.89							WORKING AREA: 50m x 50m	38																																																																																																																																																			
39	L8C	D30	M3.7	241.98	258.73		-13.50	9454.27	145.38	40.16													286372.12	963110.32							WORKING AREA: 80m x 80m	39																																																																																																																																																			
40	L8C	D60	E3.7	275.47	265.06	254.65	35.66	9729.75	139.96	48.16												286606.59	963254.91					BURN	WORKING AREA: 80m x 80m & PROPOSED CONDUCTOR PULLING POSITION	40																																																																																																																																																					
41	L8C	D60	E14.6	254.65	248.88		38.90	9984.40	116.60	59.13													286860.62	963237.15							WORKING AREA: 80m x 80m	41																																																																																																																																																			
				243.11																																																																																																																																																																															

SSE DRAWING NUMBER :														LSTC DOC REF : 02_230796_12 RevG																																																																	
				<table><tr><td>LINE</td><td colspan="5">Strathy Wood - Connagill (Towers 19 to 64)</td></tr><tr><td>VOLTAGE</td><td colspan="5">132kV / 275kV</td></tr><tr><td>No 1 CIRCUIT ID</td><td colspan="5">Strathy Wood</td></tr><tr><td>No 1 CIRCUIT COLOUR CODE</td><td>T.B.C</td><td></td><td></td><td></td><td></td></tr><tr><td>No 2 CIRCUIT ID</td><td colspan="5">Strathy South</td></tr><tr><td>No 2 CIRCUIT COLOUR CODE</td><td>T.B.C.</td><td></td><td></td><td></td><td></td></tr></table>				LINE	Strathy Wood - Connagill (Towers 19 to 64)					VOLTAGE	132kV / 275kV					No 1 CIRCUIT ID	Strathy Wood					No 1 CIRCUIT COLOUR CODE	T.B.C					No 2 CIRCUIT ID	Strathy South					No 2 CIRCUIT COLOUR CODE	T.B.C.					<table><tr><td>PHASE CONDUCTOR SIZE</td><td colspan="2">500mm² AAAC RUBUS</td></tr><tr><td>EARTHWIRE CONDUCTOR SIZE / OPGW</td><td colspan="2">48f OPGW KEZIAH EQ.</td></tr><tr><td>MINIMUM GROUND CLEARANCE</td><td colspan="2">6.7m / 7.0m</td></tr><tr><td>DESIGN TEMPERATURE</td><td colspan="2">90°C</td></tr><tr><td>CONTRACTOR</td><td colspan="2">T.B.C.</td></tr><tr><td>CONSTRUCTION DATE</td><td colspan="2">T.B.C.</td></tr></table>				PHASE CONDUCTOR SIZE	500mm² AAAC RUBUS		EARTHWIRE CONDUCTOR SIZE / OPGW	48f OPGW KEZIAH EQ.		MINIMUM GROUND CLEARANCE	6.7m / 7.0m		DESIGN TEMPERATURE	90°C		CONTRACTOR	T.B.C.		CONSTRUCTION DATE	T.B.C.		<table><tr><td rowspan="3">STRATHY WOOD PHASE COLOURING:</td><td>TOP:</td><td rowspan="3">T.B.C.</td></tr><tr><td>MIDDLE:</td></tr><tr><td>BOTTOM:</td></tr><tr><td rowspan="3">STRATHY SOUTH PHASE COLOURING:</td><td>TOP:</td><td rowspan="3">T.B.C.</td></tr><tr><td>MIDDLE:</td></tr><tr><td>BOTTOM:</td></tr></table>		STRATHY WOOD PHASE COLOURING:	TOP:	T.B.C.	MIDDLE:	BOTTOM:	STRATHY SOUTH PHASE COLOURING:	TOP:	T.B.C.	MIDDLE:	BOTTOM:		
LINE	Strathy Wood - Connagill (Towers 19 to 64)																																																																														
VOLTAGE	132kV / 275kV																																																																														
No 1 CIRCUIT ID	Strathy Wood																																																																														
No 1 CIRCUIT COLOUR CODE	T.B.C																																																																														
No 2 CIRCUIT ID	Strathy South																																																																														
No 2 CIRCUIT COLOUR CODE	T.B.C.																																																																														
PHASE CONDUCTOR SIZE	500mm² AAAC RUBUS																																																																														
EARTHWIRE CONDUCTOR SIZE / OPGW	48f OPGW KEZIAH EQ.																																																																														
MINIMUM GROUND CLEARANCE	6.7m / 7.0m																																																																														
DESIGN TEMPERATURE	90°C																																																																														
CONTRACTOR	T.B.C.																																																																														
CONSTRUCTION DATE	T.B.C.																																																																														
STRATHY WOOD PHASE COLOURING:	TOP:	T.B.C.																																																																													
	MIDDLE:																																																																														
	BOTTOM:																																																																														
STRATHY SOUTH PHASE COLOURING:	TOP:	T.B.C.																																																																													
	MIDDLE:																																																																														
	BOTTOM:																																																																														
TOWER				SPAN LENGTH (m)	WIND SPAN	SECTION LENGTH (m)	ANGLE OF DEVIATION (+ve RIGHT -ve LEFT)	CHAINAGE	GROUND LEVEL	STRUCTURE HEIGHT (G.L. TO PEAK)	ATT.PT (BASED ON TYPICAL SUSP'N INSULATOR)	PHASE INSULATORS					OPGW INSULATORS			PROFILE DRAWING REF.	ROUTE CENTRELINE COORDINATES		JUMPER WEIGHTS - CCT1	JUMPER WEIGHTS - CCT2	VIBRATION DAMPERS - PHASES	VIBRATION DAMPERS - OPGW	CROSSINGS / INFRINGEMENTS IN SPAN	REMARKS	TOWER NO																																																		
NO	SPEC	TYPE	BODY EXT										NO OF STRINGS	UNIT RATING	UNITS PER STRING	ARC GAP	DRAWING REF.	CONDUCTOR TERMINATION	ADDITIONAL INSULATOR WEIGHT (IF REQ)	UNIT RATING	DRAWING REF.	CONDUCTOR TERMINATION		EASTING	NORTHING																																																						
41	L8C	D60	E14.6		248.88		38.90	9984.40	116.60	59.13													286860.62	963237.15							WORKING AREA: 80m x 80m	41																																															
				243.11																																																																											
42	L8C	D	M2.4		243.09			10227.51	130.95	43.99													287038.70	963071.66							WORKING AREA: 50m x 50m	42																																															
				243.06																																																																											
43	L8C	D	E2.4		238.98			10470.57	133.60	48.87													287216.75	962906.19							WORKING AREA: 50m x 50m	43																																															
				234.90																																																																											
44	L8C	D30	STD		242.90		9.05	10705.46	136.94	43.82													287388.82	962746.29							WORKING AREA: 80m x 80m	44																																															
				250.91																																																																											
45	L8C	D	E3.7		250.53			10956.37	126.66	50.09													287543.46	962548.70							WORKING AREA: 50m x 50m	45																																															
				250.16																																																																											
46	L8C	D	E3.7		287.19			11206.53	108.11	50.09													287697.64	962351.71							WORKING AREA: 50m x 50m	46																																															
				324.21																																																																											
47	L8C	D	STD		252.61			11530.74	106.66	46.43													287897.46	962096.39							WORKING AREA: 50m x 50m	47																																															
				181.00																																																																											
48	L8C	D	M1.2		191.46			11711.74	103.01	45.21													288009.02	961953.86							WORKING AREA: 50m x 50m	48																																															
				201.91																																																																											
49	L8C	D30	E3.7		213.15		12.81	11913.65	101.12	47.47													288133.46	961794.86							WORKING AREA: 80m x 80m &	49																																															
				224.40																																																																											
50	L8C	D	STD		225.34			12138.05	100.40	46.43													288229.13	961591.87							WORKING AREA: 50m x 50m	50																																															
				226.27																																																																											
51	L8C	D	E2.4		220.09			12364.32	72.87	48.87													288325.60	961387.20							WORKING AREA: 50m x 50m	51																																															
				213.91																																																																											
52	L8C	D	STD		192.71			12578.23	57.50	46.43													288416.80	961193.70							WORKING AREA: 50m x 50m	52																																															
				171.52																																																																											
53	L8C	D	E4.9		226.88			12749.75	41.30	51.31													288489.93	961038.56							WORKING AREA: 50m x 50m	53																																															
				282.23																																																																											
54	L8C	D60	E3.7		248.73		-34.48	13031.98	41.73	48.16													288610.26	960783.26							WORKING AREA: 80m x 80m & PROPOSED CONDUCTOR PULLING POSITION	54																																															
				215.23																																																																											
55	L8C	D	E3.7		213.07			13247.21	53.50	50.09													288796.11	960674.72							WORKING AREA: 50m x 50m	55																																															
				210.92																																																																											
56	L8C	D	E3.7		211.35			13458.13	65.20	50.09													288978.25	960568.34							WORKING AREA: 50m x 50m	56																																															
				211.78																																																																											
57	L8C	D30	STD		201.63		27.46	13669.91	50.05	43.82													289161.12	960461.54							WORKING AREA: 80m x 80m	57																																															
				191.48																																																																											
58	L8C	D	E4.9		201.94			13861.39	26.77	51.31													289263.30	960299.60							WORKING AREA: 50m x 50m	58																																															
				212.40																																																																											
59	L8C	D	E8.5		220.92			14073.79	16.16	54.97													289376.65	960119.97							WORKING AREA: 50m x 50m	59																																															
				229.44																																																																											
60	L8C	D	E2.4		207.89			14303.23	25.84	48.87													289499.08	959925.93							WORKING AREA: 50m x 50m	60																																															
				186.34																																																																											
61	L8C	D60	STD		210.60		-30.08	14489.57	35.86	44.50													289598.52	959768.34							WORKING AREA: 80m x 80m & PROPOSED CONDUCTOR PULLING POSITION	61																																															
				234.87																																																																											
62	L8C	D30	M3.7		241.05			14724.44	31.40	40.16													289806.53	959659.28							WORKING AREA: 80m x 80m	62																																															
				247.24																																																																											
63	L8C	D	E3.7		257.30			14971.70	23.60	50.09													290047.66	959604.68							WORKING AREA: 50m x 50m	63																																															
				267.37																																																																											
64	L8C	DT	STD		133.69			15239.07	24.52	46.33													290308.48	959545.82							WORKING AREA: 80m x 80m & PROPOSED CONDUCTOR PULLING POSITION	64																																															